











70 SERIE 40/60/80 MODULE


| | Code | Inhoud in liters | | Afm. in cm. BxDxH | kW/V | EUR |
|---|--------------------------|---------------------|---|----------------------|----------|-----------------|
|  | <u>Elektrisch</u> | | | | | |
| | FE7117 | 17 |  | 40x70x85/90 | 16,5/400 | 2.511,-- |
| | FE7207 | 8+8 |  | 40x70x85/90 | 14,0/400 | 3.235,-- |
| | FE7215 | 15+15 |  | 60x70x85/90 | 20,4/400 | 3.498,-- |
| | FE7217 | 17+17 |  | 80x70x85/90 | 33,0/400 | 4.294,-- |
| | <u>Gas</u> | | | | | |
|  | FG7117T | 17 |  | 40x70x90 | 17 kW | 2.813,-- |
| | FG7207T | 8+8 |  | 40x70x90 | 12 kW | 3.742,-- |
| | FG7215T | 13+13 |  | 60x70x90 | 18,8kW | 3.917,-- |
| | FG7217T | 17+17 |  | 80x70x85/90 | 33 kW | 4.978,-- |

FG7217T

De FG modellen hebben een 1x230V aansluiting

MELT FRITEUSES

Melting trapsgewijs temperatuuropbouw van 0-100°C.







Voorbeeld van een frituur "Melting" cyclus.

1. Start van de cyclus (leeg).
2. Temperatuurval na vullen.
3. Snelle temperatuurcorrectie.



FG7117MT

| | | | | | |
|--------------------------|-------|---|-------------|-------------|-----------------|
| <u>Elektrisch</u> | | | | | |
| FE7117MT | 17 |  | 40x70x85/90 | 16 kW/400 | 2.899,-- |
| FE7215MT | 13+13 |  | 60x70x85/90 | 20,4kW/400 | 3.820,-- |
| <u>Gas</u> | | | | | |
| FG7117MT | 17 |  | 40x70x85/90 | 16,5 kW/230 | 3.399,-- |
| FG7215MT | 13+13 |  | 60x70x85/90 | 18,8 kW/230 | 4.665,-- |

Wijzigingen voorbehouden